

WET DRY

GapVax

25
Years of Excellence



UNIT SHOWN WITH OPTIONS



HV56 SERIES

Hydro-Excavator

WATER DRY POWER PERFORMANCE VERSATILITY.



VACUUM SYSTEM:

Positive Displacement Pump; 5,250 CFM, 28" Hg; 500 HP Transfer Case with air-shift engagement. Specially designed ultra-quiet air injection and discharge silencers. The HV-56 comes standard with a tailgate porthose (boom options are available).

FILTRATION:

Our patented wet/dry single-mode filtration system includes a top loading debris tank, debris body baffle, a 12" stainless steel floatball shutoff, six cyclone centrifugal material separators, 40 Snap-ring type filters with heavy-duty galvanized cages, and a safe working area on top of the collector body.

DEBRIS BODY:

Our unique design offers a unitized water and debris tank with long sill frame. The HV-56 offers a 15 cubic yard debris body made from 1/4" EXTEN steel. Full opening tailgate with field-adjustable hinge and dual cylinders. Four fail-safe, individually adjustable locks that assure a complete seal. Heavy-duty, double acting lift cylinder provides a stable 45° dump angle.

WATER SYSTEM

Water tank capacity options of 400, 550, 750, 1,000 or 1,200 gallons. The tri-plex water pump is direct-shaft driven via the transmission PTO. The water pump flow ranges from 5-40 gpm with a pressure from 2,000-5,800 PSI. The standard hose reel is 1/2" x 50' (100-200' reel options are available)

Other Features include:

We pride ourselves on custom-manufacturing a top of the line, all-around excellent product. With noise and vibration dampening mounts on the blower and transfer case; high-efficiency, low maintenance all steel air duct construction with clean out access; 20" body access manway; full bearing body pivot; heavy-duty electric vibrator with thermal overload protection; super heavy-duty rear splash plate; body and tailgate safety props...the list goes on and on.

See full lists of features and options on our website.

OPTIONS:

- Vacuum loading boom, 18', 22', or 25' reach from center of truck
- Stainless steel water and/or debris body
- Heated cabinets for pump and hose reel
- Water heater
 - 400,000 BTU or 575,000 BTU
- Hydrostatically driven water pump
- Water recirculation systems
- Glycol injection
- Liquid load indicator
- Various toolboxes, tube racks, and tube tray options
- Auxiliary lift axles
- Auger unloading system
- Body pressurized system
- Various lighting options
- Remote pendant or wireless controls

See website for complete listing

GapVax HV56
Hydro Excavator

www.gapvax.com 888-442-7829 Johnstown, PA

SPECS SUBJECT TO CHANGE WITHOUT NOTICE